



**1.CABLE:**

CONDUCTOR: 24AWG SOLID SILVER PLATED COPPER.  
 INSULATION: FOAM POLYOLEFIN.  
 PAIR: 2 SINGLES LAID FLAT AND PARALLEL.  
 PAIR DRAIN WIRE: 26AWG SOLID SILVER PLATED COPPER.  
 PAIR SHIELD: ALUMINUM/POLYESTER TAPE. ALUMINUM SIDE FACING IN, 25% OVERLAP. COLOR-YELLOW.  
 INNER SHIELD: ALUMINUM/POLYESTER TAPE, ALUMINUM SIDE PACING OUT, 25% OVERLAP.  
 OUTER SHIELD: 36AWG TIN PLATED COPPER BRAID, 85% COVERAGE.  
 DIAMETER: 6.86mm NOMINAL. COLOR: BLACK.  
 PRINT LEGEND: "MADISON CABLE CORP.TYPE CL2 75°C 24AWG (UL) TurboTwin™ "  
 DIFFERENTIAL IMPEDANCE: 100±5 OHMS @TDR  
 UL LISTING: TYPE CL2 AS SPECIFIED IN ARTICLE 725 OF THE NATIONAL ELECTRICAL CODE. TurboTwin™

- 2.HOOD: ZINC DIE CASTING, NICKEL PLATING.
- 3.LATCH: PC RESIN UL94V, COLOR IN BLACK.
- 4.P.C.B.: 4 LAYERS, FR4. 30U" GOLD ON GOLDEN FINGERS, COLOR: RED.
- 5.SERIAL ID IC: AT24C02B OR EQUIVALENT.

WIRING CHART			
P1 END		P2 END	
P1 PAD	SIGNAL	P2 PAD	SIGNAL
12	RX-	19	TX-
13	RX+	18	TX+
GROUND		GROUND	
18	TX+	13	RX+
19	TX-	12	RX-
GROUND		GROUND	

△					Data	Part No.	CAB-SFP+ Cable
△					Design		
△					Check		
Revision	Data	Content	Confirm	Design	Confirm	Cisco Part No.	



**ACE PLUS CORP.**